

A/AT MODELS

Series			Std. GVWR (lbs.)	Max. GVWR† (lbs.)	Max. GCWR (lbs.)
A9513 (Heavy Duty Diesel)	113" BBC	4x2	34,700	37,600	125,000*
AT9513 (Heavy Duty Diesel)	113" BBC	6x4	48,000	54,600	125,000*
A9522 (Heavy Duty Diesel)	122" BBC	4x2	34,700	37,600	125,000*
AT9522 (Heavy Duty Diesel)	122" BBC	6x4	48,000	54,600	125,000*

See the Truck Selection Section of Component Information Data Book to determine components required for the intended application, or to compute GVWR with optional equipment.

**The standard GCWR is 80,000 lbs.; a 125,000 lb. GCWR Turnpike Rating is available with Cummins N14, Cat 3406 and DDC Series 60 engines of 350 HP and greater with RT-14609/14709, RT-14710, RTLO-14610, RTO-14709MLL, RTLO-14713, RT-14713, RTX-15710, RTLO-15610, RTO-14908LL, RTX-16709, RTX-16710, RTLO-16710, RTLO-16713, RT-15715, RTL-15710, RTL-16710, FRO-15210, FRO-16210 and RTLO-18718 transmissions and 23,000 lb rear axle (RS-23-180) or 40,000 lb. rear axle (RT-40-145).*

See Transmission and Rear Axle sections of the Component Book and Supplier application guidelines for details and exceptions to these general guidelines.

† A DSO wheelbase may limit the max. GVWR of a vehicle. Contact the DSO group at the truck plant for actual ratings.

INVOICE CHARGES	
Destination	\$875.00 (U.S.)
Fuel, U.S. Gallons – w/Single Fuel Tank (up to 150 gal.)	21 gal.
– w/Dual or Mixed Capacity Fuel Tanks (up to 150 gal. per tank)	46 gal.
– w/Single Fuel Tank (150 gal.)	46 gal.
– w/Dual Fuel tanks (150 gal. per tank)	96 gal.